


DATA SHEET

CARBOPOMP/M

Long length hose suitable for delivery of petrol, diesel and biodiesel to engine on private boats up to 24 mt. Complying **SAE J 1527 : 2004 USCG-A1- ISO 7840:2004 A1 CE**
Homologated DIP 128405/MI/1 0474 R.I.NA and nr. 06/00078 LLOYD'S REGISTER. Registered: NMMA Nr. 2459118 and Nr. 2459119



Technical Characteristics

Tube	Black smooth synthetic rubbers suitable for petroleum products up to 50% aromatic content, 15% oxygenated compound, biodiesel, ecological fuel.
Reinforcement	High strength textile plies
Cover	Black smooth self-extinguishing rubber resistant to abrasion, heat, oil and marine environment.
Temperature	- 20°C + 80°C
Marking	 ITALY CARBOPOMP® MARINE FUEL SAE J1527:2004 USCG A1 - ISO 7840:2004 A1 CE - 0474 RINA - LLOYD'S REGISTER (Ø/year) (in white letters)

Registered: **NMMA Nr. 2459118 and Nr. 2459119**
5 YEARS GUARANTEE

Sizes

Diametro interno nominale Nominal Inner Diameter	Diametro esterno nominale Nominal Outside Diameter	Diametro interno effettivo Real Inner Diameter	Diametro esterno effettivo Real Outside Diameter	Pressione di scoppio Nominal Burst Pressure	Peso teorico Weight	Aspirazione Vacuum
mm	mm	mm	mm	bar	Kg/m	kpa
6	16	6	15	> 14	0.215	80
8	17	8	16	> 14	0.220	80
10	19	10	18	> 14	0.255	80
12	22	12	21	> 10	0.340	35
16	26	16	25	> 10	0.420	35
19	30	19	29	> 10	0.550	35
25	35	25				